

- DESCRIPTION** Fritz FL-7 is a powdered fluid loss additive recommended for blending with cement to control the loss of filtrate from a cement slurry.
- ADVANTAGES**
- FL-7 is a blend of a modified cellulose and dispersant used to control the loss of water from a cementing system when pumped or squeezed against a porous environment.
 - It also functions as a cement retarder and may increase the viscosity of a slurry.
 - It may be used in wells having bottom hole circulating temperatures from 60 to 250°F. (16 C to 121 C)
- APPLICATION**
- FL-7 may be used for fluid loss control in any API class of cement (A, C, G, or H).
 - It may be used with other cement additives such as dispersants, silica flour, retarders, defoamers and weighting materials.
 - FL-7 is not recommended for use in slurries with salt concentrations of 18% bww or greater.
- PROPERTIES**
- Light Tan Powder
 - Specific Gravity – 1.22
 - Bulk Density – 36.6 lb./cu.ft.
 - Solubility limited by resultant viscosity
 - Water Requirements – 0.4 to 0.5 gal./sk
 - pH – 6.5
 - Loading Rate – 0.4 to 1.5% bwc
 - Packaged in 50 lb. bags

The information contained herein is based on data considered accurate with representative samples. However, no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. The above data does not imply specifications for this product. Fritz Industries, Inc. assumes no responsibility for personal injury or property damage to vendees, users or third parties, caused by the material. Such vendees or users assume all risks associated with the use of the material. Consult the Material Safety Data Sheet before using this product.