

DESCRIPTION OB-2 is a conventional oxidizing breaker. The oxidizing agent in OB-2 is sodium persulfate. OB-2 is effective in applications from 130 to 200°F, and break times can be tailored by varying the concentration added. Below 130°F, an activator needs to be added to the fluid in order to break the fluid. OB-2 can be packaged and labeled to your requirements, including water-soluble bags.

- ADVANTAGES**
- OB-2 is a powder that is readily soluble in water on location.
 - OB-2 can be packaged and labeled to meet your requirements, including in water-soluble bags.

- APPLICATION**
- OB-2 is used to break guar or derivatized guar based fluids. The applicable temperature range for OB-2 is 130 – 200°F.
 - Below 130°F, a breaker activator can be added to the fracturing fluid to extend the usefulness of OB-2 below 130°F.

- PROPERTIES**
- White Powder
 - Specific Gravity – 2.6
 - Bulk Density – 71 to 81 lb./ft.³
 - Solubility in water – 43% at 77°F (25 C)
 - pH (1 % in water) – 6 to 8
 - Activity – 99%

The information contained herein is based on data considered accurate with representative samples. However, no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. The above data does not imply specifications for this product. Fritz Industries, Inc. assumes no responsibility for personal injury or property damage to vendees, users or third parties, caused by the material. Such vendees or users assume all risks associated with the use of the material. Consult the Material Safety Data Sheet before using this product.