

- DESCRIPTION** Pump Flush Plus is a blend of solvents and surfactants for flushing chemical pumps, liquid additive pumps and pump lines.
- ADVANTAGES**
- Pump Flush Plus is oil-soluble, water-soluble and biodegradable. It will help cut the oil as well as remove any residual polymer.
 - It will increase the life of the pump rotors and stators as well as removing buildup, which has occurred that could lead to contamination or plugging.
 - It is non-sheening and non-toxic.
- APPLICATION**
- Pump Flush Plus can be pumped ahead of polymer oil suspensions to flush water and residual materials from the lines and pumps. After the job, the liquid additive pump and lines can also be cleaned.
 - Pump Flush Plus is ideal for use with cementing fluid loss additive suspensions as well as guar and guar derivative suspensions used for stimulation treatment.
- PROPERTIES**
- Clear Colorless Liquid
 - Specific Gravity – 0.80
 - Bulk Density – 6.67 lb./gal.
 - Pump Flush Plus is soluble in water
 - Packaged in 5 gallon pails and 55 gallon drums
 - Flash Point – 160°F (71 C)
 - It is recommended that 5 to 15 gallons be pumped ahead of and behind polymer suspensions.

The information contained herein is based on data considered accurate with representative samples. However, no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. The above data does not imply specifications for this product. Fritz Industries, Inc. assumes no responsibility for personal injury or property damage to vendees, users or third parties, caused by the material. Such vendees or users assume all risks associated with the use of the material. Consult the Material Safety Data Sheet before using this product.